## VIEW<sup>™</sup> | 7" Touchscreen

TL700 - 7" Touchscreen

The TL700 is an IP-Based in-wall touchscreen keypad featuring a high resolution, color LCD touch panel, designed for a VIEW system. The TL700 features a 2-port Ethernet switch and two 4-pin Phoenix connectors for communications, power, and cascading one IP-Based Amplifier / Room Controller.

# **ClearOne**



## IP-BASED IN-WALL TOUCHSCREEN

## **APPLICATIONS**

- + Audio/Video Routing Control
- + Source Selection
- + Source Transport Control
- + Audio Level Control
- + Control and Display of Camera Images
- + Multi-room System Control
- + HVAC Control
- + Lighting Control
- + Control of Displays
- + Projection Screen/Projector Lift Control
- + Paging/Intercom

### **ADVANTAGES**

- + The VIEW TL700 uses a touch sensitive color LCD panel to display controls, metadata, and content. The TL700 includes a 7" TFT color LCD screen.
- + The VIEW TL700 interface allows control of all aspects of a VIEW system, displays metadata regarding the audio/video source or control system, and displays images from IP cameras.
- + The intuitive user interface allows the user to assume control over other zones or to control multiple zones.
- + "Skins" can be selected that blend the screen's look with the color and style of the room.
- + Supports over 15 languages and international language meta data.
- + Includes a built in microphone allowing for paging and zone monitoring over the VIEW network.
- + Included is a built in IR Receiver that recognizes all VIEW Discreet IR commands and supports network IR passthrough of all other IR signals.
- + Each TL700 includes a white trim plate, but color kits (sold separately) are available in almond, ivory, and black.

The Power of AV over IP™





#### > TL700 - 7" **REAR PANEL**



#### > SPECIFICATIONS

#### TL700 - 7" Diagonal LCD Touchscreen

**Resolution** 800 x 480

**Viewing Angle** 65° Horizontal 50° Vertical

#### **IR Control Sensor**

Current (mA) 250

Operating Temperature (BTU/hr) 23.87

#### Connections

Two (2) Ethernet RJ45 Port Switches

One (1) 4-pin Power In Phoenix Connector

One (1) 4-pin Power Out Phoenix Connector

#### In-Wall Dimensions (W x H x D)

7 1/16" x 4 15/16" x 1 1/4" (180mm x 126mm x 32.2mm)

External Dimensions: (W x H x D) 7.875" x 4.9375" x 1.5625" (200mm x 146mm x 39.7mm)

Weight: 1 lb 6 oz (0.612 kg)

NetPower™

1

#### Compliance

Restriction of use of certain Hazardous Substances (RoHS) compliant CE C-Tick

#### Accessories

TLB700 Rough-in Box

Part Number TL700

## Powered by StreamNet™

#### > CLEARONE LOCATIONS

Headquarters: Salt Lake City, UT USA 5225 Wiley Post Way Suite 500 Salt Lake City, UT 84116 Tel: 801-975-7200 Toll Free: 800-945-7730 Fax: 801-977-0087 sales@clearone.com Latin America Tel: 801-974-3621 global@clearone.com EMEA Tel: 44 (0) 1189 036 053 global@clearone.com APAC Tel: 801-303-3388 global@clearone.com

© 2011 ClearOne. All rights reserved. Other product names may be trademarks of their respective owners. Information in this document subject to change without notice. 802-000-040-DS Rev. 1.1 - April 2011.