



VIEW® Lite is the newest and most economical addition to our AV over IP Streaming line. It provides essential functionality that meets the full needs of simple AV over IP applications while simultaneously delivering superb price-to-performance value.

VIEW Lite is a JPEG2000 compression technology based solution, with very low latency at about 1.5 frames, end-to-end, with resolutions of 4K60 with 4:2:0 color space; and 4K30 and 1080p60 with 4:4:4 color space support for ultra high-quality live video streaming and distribution applications over a dedicated IP network.

### VIEW Lite Features

- + Lowest priced AV over IP streaming solution
- + JPEG2000 codec standard technology
- + Very low end-to-end latency of around 1.5 frames
- + High bandwidth requirement of around 850 Mbps
- + 4K60 resolution with 4:2:0 color space support
- + 4K30, 1080p60 resolution with 4:4:4 color space support
- + HDCP for content protection
- + USB HID control through keyboard/mouse
- + IR and RS232 control
- + Local loopback output
- + PoE and DC power



### APPLICATIONS

Corporate

Education

Hospitality

Entertainment


Transportation

Houses of Worship

### Front Panel



### Back Panel



## PRODUCT SPECIFICATIONS

### Control

#### Serial RS232 Port:

RS232 Pins TX, RX, G are used for device troubleshooting only  
Pins G, RX, TX are used for controlling, configuring and managing system  
Pins G, 12V are used for providing a 12 VDC 0.5 A output

#### LAN1 (AV/PoE):

RJ-45 Ethernet jack with PoE support  
IEEE 802.3AF PoE PD standard  
10/100/1000Mbps Ethernet Port  
Connects to a switch for communication with encoders and decoders on the same network.

#### LAN2 (C):

RJ-45 Ethernet jack without PoE.  
Used for 3<sup>rd</sup>-party controller controlling, configuring and managing system.

### General

#### Reset:

Factory reset by pressing the button continuously for 5 seconds

#### LEDs:

Indicator	Response
Status	Illuminates Blue when IP controller is working properly; otherwise LED is off.
Power	Illuminates Red when power is applied from PoE or external power supply.

#### Power:

12V 1A DC power supply with locking (included)

### Mechanical

#### Dimensions (W x H x D):

3.67" × 1.02" × 5.46"  
(93mm × 26mm × 139mm)

#### Weight:

0.84 lbs (0.38 kg)

#### Mounting:

Mounting ears included

#### Operating Temperature:

32 to 104 °F (0 to 40 °C)


### Part Number

**VIEW Lite Controller CJ100:** 910-0100-003

### Other VIEW Lite Products

**VIEW Lite Encoder EJ100:** 910-0100-001

**VIEW Lite Decoder DJ100:** 910-0100-002



## SALES AND INQUIRIES

Headquarters	US & Canada	International	Sales	TechSales	TechSupport
5225 Wiley Post Way, Suite 500 Salt Lake City, UT 84116	Tel: 801.975.7200 TollFree: 800.945.7730 Fax: 801.303.5711	Tel: +1.801.975.7200 global@clearone.com	Tel: 801.975.7200 sales@clearone.com	Tel: 801.974.3760 techsales@clearone.com	Tel: 801.974.3760 tech.support@clearone.com