


CONVERGENCE® InSite Server



CONVERGENCE InSite Server is network hardware that enables bi-directional communications between Cloud AV Manager or Enterprise AV Manager and on-site ClearOne Pro Audio devices.

One Site, One Server

Set up CONVERGENCE hassle free with one InSite Server for multiple subnets and VLANs.

- > The CONVERGENCE Local Agent software comes pre-installed and ready to deploy.
- > InSite Server setup and registration is simple and painless using a web browser.
- > Get up and running quickly with auto discovery of all supported devices on multiple subnets without the need for labor-intensive, individual device registration.
- > Plenty of internal storage for InSite logs and backup configuration files of managed devices.
- > Small footprint with a solid-state drive, auto power on, and a fanless enclosure for 24/7 high reliability.
- > Includes extra ports for additional network connections, or optional keyboard, video, and mouse for servicing.
- > InSite Server is a convenient alternative to the downloadable CONVERGENCE Local Agent software that must be self-installed.
- > Integrates with third-party management systems via a RESTful web interface.

APPLICATIONS:

- Local AV System Maintenance
- Device Status Monitoring
- Remote AV Device Control
- Equipment Auditing
- Help Desk Operations
- Single-pane-of-glass Business Intelligence

USERS:

- Office Buildings
- Convention Centers
- Educational Institutions
- Corporate Campuses
- Global Enterprises
- Multi-site Organizations
- Large Government Deployments



Fast Firm Foundation

The Local Agent software is the foundation of a CONVERGENCE AV Manager system. Using the InSite Server makes laying that foundation fast and firm.

Great Ideas Need to be Heard and Seen!™

CONVERGENCE InSite Server

HARDWARE SPECIFICATIONS

- Dimensions: 17.2 x 12.5 x 3.8 cm (6.77 x 4.92 x 1.5 in.)
- Weight: 1.2 kg (2.65 lb)
- Case Material: Aluminum alloy
- Power: 12V power input, comes with 12V 5A power adapter; On/Off switch and Last State Auto Power On
- Cooling: Passive Heat Sink (fanless)
- Connectivity: USB 3.0 x 4, USB 2.0 x 2, LAN Port (1 x RJ45, Gigabit Ethernet)
- Video: HDMI, VGA dual display (not required for setup or use)
- 2-Year Warranty
- Serves up to 4,000 devices

SOFTWARE SPECIFICATIONS

- Operating System: Linux
- Software Preinstalled: CONVERGENCE Local Agent AV Manager
- Browsers supported (desktop and mobile): Firefox, Chrome, Edge, Safari

COMMUNICATIONS

- Central Hub Connections: CONVERGENCE Cloud AV Manager or CONVERGENCE Enterprise AV Manager.
- Web server protocol: HTTP (port 8080)
- Minimum broadband Internet connection speed: 256 Kbps (512 Kbps recommended)
- Remote access: Cloud AV Manager, Enterprise AV Manager, SSH, VPN
- UDP and TCP audio device packet data on ports 3602, 3601, and 4912
- UDP broadcast, UDP unicast and direct TCP connection via scanning, on multiple subnets
- FTP for auto and remote updates

PRODUCTS SUPPORTED

- CONVERGE® Pro 2 DSP Mixers and all P-Link enabled devices
- CONVERGE Huddle DSP Mixer and all Huddle Expansion devices

SECURITY

- Installation behind Internet firewall recommended
- SHA-256 encrypted password storage for users, devices, and external services
- Password trial rate limiting
- Quality meters prevent weak passwords

PART NUMBER

- 910-1000-001

SALES AND INQUIRIES

Headquarters

5225 Wiley Post Way
Suite 500
Salt Lake City, UT 84116

US & Canada

Tel: +1.801.975.7200

International

Tel: +1.801.975.7200

Sales

Tel: +1.801.975.7200
sales@clearone.com

Tech Support

Tel: +1.801.974.3760
audiotechsupport@clearone.com